




60° / 90°
NC Deburring Tool

Retain exceptional
positional accuracy
of the deburring depth and diameter

Higher feed deburring and chamfering on CNC machine

Insert

- Ideal for fine hole deburring.
- TiAlN coated carbide insert can stand very long life.



3 Flutes,
2 cutting edge.



6 Flutes,
Single cutting edge.

● Best ◎ Suit ○ Possible


Grade	P	M	K	N
NC2032	●	●	●	●
XP9001	○	○	◎	●

Flutes	Angle	Code	Part No.	Coating	Grade	Dimensions	Tmin.	Tmax.	
									L
NEW 3	60°	01X611	X060A60T3-NC2032	TiAlN	K20F			0.1	1.0
		01X612	X060A60T3-XP9001	-					
	90°	01X911	X060A90T3-NC2032	TiAlN					
		01X912	X060A90T3-XP9001	-					
6	60°	01X601	X060A60T6-NC2032	TiAlN	K20F			0.1	1.9
	90°	01X901	X060A90T6-NC2032	-				0.5	2.0

Holder

- One holder supports the entire X060 series inserts.

Cylindrical Shank



Code	Parts No.	Shank	Ød	L	Screw / Key
69X001	00-99619-X060-06	Steel	6	40	NS-22044 0.9Nm / NK-T7
69X002	00-99619-X060-06L	Carbide	6	60	
69X003	00-99619-X060-06LS	Steel	6		
69X004	00-99619-X060-06XL	Carbide	6	100	

Integrated ER16 taper-shank

Parts No.:00-99816-X060

